














FILM CAPACITORS

We offer a full line of standard film capacitor products used as filters, DC link and snubbers for power electronics applications. Only the industry's highest grades of metallized films are used to ensure the best possible performance. Better yet, you can count on our engineering experts to provide assistance with any custom film capacitor design if the standard won't do.



Axial Polyester

Type	Construction	Form Factor	Temperature (°C)	Voltage (Vdc)	Capacitance Range(μF)
WMF	Film/Foil		-55 to +125	50-630	.001-5
WMC	Film/Foil		-55 to +125	80-400	0.001-0.47
MMP	Metallized		-55 to +125	100-630	0.01-10.0
MMWA	Metallized		-55 to +125	50-1000	0.01-10.0
150	Metallized		-55 to +125	63-1000	0.01-10.0
430P	Metallized		-55 to +85	Up to 600	0.047-10
430PHV	Metallized		-55 to +85	Up to 10K	.0047 - .39
470P	Film/Foil		-55 to +85	50-630	.01 - 1
460M	Metallized		-55 to +85	63-400	0.022-100
461M	Metallized		-55 to +85	63-400	0.027-100
462M	Metallized		Metallized	Up to 2000	0.1 - 6.8
463M	Metallized		-55 to +85	Up to 2000	0.1 - 6.8
481M	Metallized		-55 to +85	300	3.96