








# QUICK REFERENCE TABLE DIP SWITCHES

# 機種選択表

## ■ DIP スライドスイッチ DIP SLIDE SWITCHES

	CVS	CHS	CHP	CFS	CFP
シリーズ名 Series name					
回路構成 Structure of circuit	1 bit 2 bits 3 bits 4 bits 8 bits	1 bit 2 bits 4 bits 6 bits 8 bits 10 bits	2 bits 4 bits 8 bits	1 bit 2 bits 3 bits 4 bits 5 bits 6 bits 7 bits 8 bits 9 bits 10 bits	2 bits 3 bits 4 bits 5 bits 6 bits 8 bits 10 bits
接点定格 Contact rating	Non-switching : DC50 V 100 mA Switching : DC6 V 100 mA DC24 V 25 mA				
端子間ピッチ Terminal spacing	1 mm pitch	Half pitch (1.27 mm)		Full pitch (2.54 mm)	
接触抵抗 Contact resistance	200 mΩ maximum	50 mΩ maximum			
シール性 Sealing	洗浄不可 Non sealed construction	テープシール付き洗浄可能タイプ有り Washable type available with seal tape	洗浄不可 Non sealed construction	テープシール付き洗浄可能タイプ有り Washable type available with seal tape	洗浄不可 Non sealed construction
表面実装対応 Surface mounting	○				
外形寸法 Dimensions	4.7 × 2 × 1.45 mm (1 bit) 4.7 × 3 × 1.45 mm (2 bits) 4.7 × 4 × 1.45 mm (3 bits) 4.7 × 5 × 1.45 mm (4 bits) 4.7 × 9 × 1.45 mm (8 bits)	5.4 × 2.5 × 2.5 mm (1 bit) 5.4 × 4.1 × 2.5 mm (2 bits) 5.4 × 6.6 × 2.5 mm (4 bits) 5.4 × 9.2 × 2.5 mm (6 bits) 5.4 × 11.7 × 2.5 mm (8 bits) 5.4 × 14.3 × 2.5 mm (10 bits)	5.9 × 4.6 × 4.6 mm (2 bits) 5.9 × 7.1 × 4.6 mm (4 bits) 5.9 × 12.2 × 4.6 mm (8 bits)	(スルーホール Through hole) 6.4 × 3.95 × 4.5 mm (1 bit) 6.4 × 6.5 × 4.5 mm (2 bits) 6.4 × 9.05 × 4.5 mm (3 bits) 6.4 × 11.6 × 4.5 mm (4 bits) 6.4 × 14.15 × 4.5 mm (5 bits) 6.4 × 16.7 × 4.5 mm (6 bits) 6.4 × 19.25 × 4.5 mm (7 bits) 6.4 × 21.8 × 4.5 mm (8 bits) 6.4 × 24.35 × 4.5 mm (9 bits) 6.4 × 26.9 × 4.5 mm (10 bits)	8.6 × 7.5 × 6.7 mm (2 bits) 8.6 × 10.05 × 6.7 mm (3 bits) 8.6 × 12.6 × 6.7 mm (4 bits) 8.6 × 15.15 × 6.7 mm (5 bits) 8.6 × 17.7 × 6.7 mm (6 bits) 8.6 × 22.8 × 6.7 mm (8 bits) 8.6 × 27.9 × 6.7 mm (10 bits)
掲載ページ Page	17	21	35	41	48

## ■ DIP スライドスイッチ DIP SLIDE SWITCHES

	CYP	CES
シリーズ名 Series name		
回路構成 Structure of circuit	2 bits 4 bits 6 bits 8 bits 10 bits	2 bits 4 bits 6 bits 8 bits
接点定格 Contact rating	Non-switching : DC50 V 100 mA Switching : DC6 V 100 mA DC24 V 25 mA	
端子間ピッチ Terminal spacing	Full pitch (2.54 mm)	
接触抵抗 Contact resistance	100 mΩ maximum	50 mΩ maximum
シール性 Sealing	テープシール付き洗浄可能タイプ有り Washable type available with seal tape	洗浄不可 Non sealed construction
表面実装対応 Surface mounting	○	
外形寸法 Dimensions	6 × 6.48 × 5 mm (2 bits) 6 × 11.56 × 5 mm (4 bits) 6 × 16.64 × 5 mm (6 bits) 6 × 21.72 × 5 mm (8 bits) 6 × 26.8 × 5 mm (10 bits)	10 × 7.66 × 10 mm (2 bits) 10 × 12.74 × 10 mm (4 bits) 10 × 17.82 × 10 mm (6 bits) 10 × 22.9 × 10 mm (8 bits)
掲載ページ Page	53	58

印刷の都合により、カタログの製品写真と実物とでは色調が異なる場合があります。  
It depends on printing state. The color of product on catalog photo may differ from the actual products.